

300V Power Racing 5W-30

Racing lubricant for racing cars

100% Synthetic – Double Ester Technology

TYPE OF USE

Racing cars with naturally aspirated or turbocharged engines, race or qualifying engines, requiring maximum power output and fastest rev raisings: Qualifying sessions, drag racing, race on tracks, Nascar, single brand races, uphill races, rallyes...

Engine designed to run low viscosity lubricants and to minimise fuel dilution in the oil.

Other applications: Gasoline or Diesel engines, turbocharged, direct injection and catalytic converters.

PERFORMANCES

STANDARDS Above existing standards.

Reference team NISMO NISSAN, Japan GT – Coloni Motorsport, Formula 3 (open wheel

cars)

Double Ester technology: maximum oil film resistance, balanced polarity, resistance at very high temperature.

Friction Modifier: maximum power output, decrease operating temperature.

0% shear loss: Stable oil pressure whatever using conditions.

Maximum anti-wear resistance.

Perfect engine cleanliness.

Low viscosity grade 5W-30 allows excellent oil flow into the engine, fastest oil pressure set up, faster rev raisings.

RECOMMENDATIONS

Oil change: according to your own use.

Can be mixed with synthetic or mineral lubricants.

PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 20°C (68°F)	ASTM D1298	0.866
Viscosity at 40°C (104°F)	ASTM D445	65 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	11 mm ² /s
HTHS viscosity at 150°C (302°F)	ASTM D4741	3.61 mPa.s
Viscosity index	ASTM D2270	162
Pour point	ASTM D97	-36°C / -33°F
Flash point	ASTM D92	218°C / 424°F
TBN	ASTM D2896	11.3 mg KOH/g